


Drum / Brush Sander

ST - 480 BDS M



Whats in the box

Combined closed stand with storage

80 grit silicon carbide / nylon brush

Aluminium drum with 80 grit abrasive

Tracking feed belt

Tool kit

Features

Standard aluminium drum plus nylon bristle / 80 grit carbide interchangeable brush

The AC inverter provides electronic variable drum speed from 200—1800 RPM for a wide range of sanding operations

Heavy duty cast iron construction for strength, rigidity & reduced vibration

Combined closed stand with castors & built-in cabinet for easy storage

Variable speed, no—give conveyer belt

Accessories

120 grit silicon carbide brush

240 Grit silicon carbide brush

Wire brush (0.4mm wire diameter)

Sandpaper strips 80—320 grit / 12 pieces set

Infeed / outfeed tables

Specifications

Max. Thickness 100mm

Min. Thickness: 0.8mm

Min. Length: sanding – 60mm

Min. Length: Brush - 90mm

Max. Width - 960mm (2 passes)

Brush speed: 200—1000 RPM

Drum speed: 200—1,800RPM

Conveyor Speed: 0-3metres / min

Conveyor Motor: Direct Drive, DC

Main motor: 1 1/2 HP single phase

Dust port: 1 x 100mm

Dimensions: 1460 x 860 x 1450mm

Net weight: 155kg